

Towbars

Nolan makes five towbar sizes, and can customize towbars to match a specific design. Our heavy-duty construction handles the heaviest loads. The square tube design adds strength. R1453 towbars have 1-1/4" diameter connecting holes; the R1451 has a 1-3/16" connecting hole. The Nolan Company can custom fabricate specific length towbars. Call us toll-free at 1-800-297-1383.

MODEL NO.	LENGTH (IN.)	WT. (LBS.)	LENGTH (mm)	WT. (kg)
R1453-1	42" (3'6")	46	1,066.80	20.87
R1453-2	96" (8')	75	2,438.40	34.02
R1451	120" (10')	92	3,048.00	41.73
R1453-3	192" (16')	135	4,876.80	61.23
R1453-4	264" (22')	175	6,705.60	79.38



Hitch Pins

STANDARD PIN-LOCK

Nolan's standard pin-lock comes complete with hairpin cotter, precision machined from high strength steel. Zinc plated with ergonomic folding handle.

MODEL NO.	SIZE (IN.)	WT. (LBS.)	SIZE (mm)	WT. (kg)
931-1	4-1/2" long x 1" dia.	2	114.30 mm x 25.40 mm	0.91



CLEVIS

Nolan's combination handle/restrainer operates with one hand and keeps pin securely in towbar. Large collar prevents pin damage. Ergonomic handle provides more leverage for easy removal. Clevis has hinged, fail-safe, 7/8" containment handle, includes 10" securement chain, and is painted red for high visibility.

MODEL NO.	SIZE (IN.)	WT. (LBS.)	SIZE (mm)	WT. (kg)
931-2	5" long x 1-1/8" dia.	6	127.00 mm x 28.58 mm	2.72



RIGID MOUNTED PINTLE HOOK

Ideal for extra-heavy duty loads and conditions, Nolan's pintle hook is easy to operate and makes positive, secure connections. High strength forged steel.

MODEL NO.	VERTICAL LOAD (LBS.)	GROSS TRAILER WT. (LBS.)	WT. (LBS.)	VERTICAL LOAD (kg)	GROSS TRAILER WT. (kg)	WT. (kg)
941-1	6,000	30,000	11	2,721.55	13,607.77	4.99
941-2	30,000	90,000	45	13,607.77	40,823.31	20.41
941-3	15,000	60,000	24	6,803.89	27,215.54	10.89

